



MATERIAL SAFETY DATA SHEET
X-100 Natural Seal Waterborne Deck Stain

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: American Building Restoration Products, Inc.
9720 S. 60th Street
Franklin, WI. 53132

Emergency Phone No. Chemtrec 1-800-424-9300

Product Trade Name: X-100 Natural Seal Waterborne
DOT Proper Shipping Name: Buffing or Polishing Compound
N.O.S.

SECTION II - HAZARDOUS INGREDIENTS

	CAS NO	AMT(%)	OSHA PEL	ACGIH TLV
Non Hazardous under the provisions of 29CFR1910	(5)	(ii)		

SECTION III - PHYSICAL DATA

Boiling Point: 212°F

Specific Gravity : approx. 1.0

Vapor Pressure (mm Hg/Deg. F.): 17.5mm @ 25°C

Vapor Density (Air=1): approx 1.0

Percent Volatile By Volume (%): 70

Solubility in Water: Dispersible

Evaporation Rate (BAC=1): approx 1.0

Appearance and Odor: White Emulsion, Ammonia Odor.

V.O.C. < 250 g/L

SECTION IV - FIRE AND EXPLOSION HAZARD

Flash Point: None.

Extinguishing Media: N/A

Special Fire Fighting Procedures: None.

Unusual Fire and Explosion Hazards: None.



MATERIAL SAFETY DATA SHEET
X-100 Natural Seal Waterborne Deck Stain

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: See Section II

Effects of Over Exposure: None.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Wash at least 15 minutes with water. If irritation persists, consult a Physician.

SKIN: Wash with soap and water.

INHALATION: No ill effects expected.

INGESTION: Do not cause regurgitation. Drink 2-3 glasses of water of milk.

SECTION VI - REACTIVITY DATA

Stability: Stable

Incompatibility: None.

Hazardous Decomposition Products: None.

Hazardous Polymerization: Will not occur.

Conditions to Avoids:

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Mop up spills immediately. Both the emulsion and the dried film may present a slippery hazard. Coagulate with either dry calcium chloride or a concentrated solution of calcium chloride, and transfer to chemical waste drum.

WASTE DISPOSAL METHOD: Contact local municipal, state, or federal agencies to ensure compliance of disposal methods with current regulations.

NOTE: Empty containers can have residues, gases or mists and are subject to proper waste disposal.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: No special protection required.

Ventilation: Normal.

Protective Gloves: Impervious.

Eye Protection: Chemical splash goggles (ANSI 2-81.1/equivalent)

Other Protective Equipment: None.



MATERIAL SAFETY DATA SHEET
X-100 Natural Seal Waterborne Deck Stain

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing: Keep from freezing.
Other Precautions:

SECTION X - PREPARATION DATE OF MSDS

Occupational Health & Safety Dept.

Date: 10/30/2007

Supersedes:

DISCLAIMER

The information contained herein is based on the data available to us and is believed to be correct. However, American Building Restoration Products, Inc. makes no warranty, expressed or implied from the use there of. American Building Restoration Products, Inc. assumes no responsibility for injury from the use of the product described herein.

X-100 Natural Seal Waterborne